3M UK PLC

3M HOUSE, PO BOX 1, MARKET PLACE,

BRACKNELL, BERKSHIRE RG12 1JU

Tel: 01344 858000

MATERIAL SAFETY DATA SHEET

Document status :

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION

Tradename:

3M(TM) DISPLAYMOUNT ADHESIVE UK-7806

3M Product ID:

GS-2000-3396-6 GS-2000-3411-3 GS-2000-3412-1 GS-2000-3413-9 GS-2000-3414-7 GS-2000-3415-4 GS-2000-3416-2 GS-2000-3417-0 GS-2000-3418-8

GS-2000-3419-6 GS-2000-3420-4

2 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient name and classification	CAS number P	ercentage
NONVOLATILE COMPONENTS		20 - 30
ACETONE	67-64-1	15 - 25
EU Hazard Symbols and Risk Phrases R:11-36-66-67)	: EU - Adaptation	25 (F,Xi;
PROPANE	74-98-6	10 - 20
EU Hazard Symbols and Risk Phrases R:12)	: EU - Adaptation	21 (F+;
DIMETYL ETHER	115-10-6	5 - 15
EU Hazard Symbols and Risk Phrases R:12)	: EU - Adaptation	21 (F+;
HEPTANES	92045-53-9	7 - 13
EU Hazard Symbols and Risk Phrases	: T; R:45-65	
HEXANES	64742-49-0	5 - 10
EU Hazard Symbols and Risk Phrases	: T; R:45-65	
BUTANE	106-97-8	3 - 7
EU Hazard Symbols and Risk Phrases	: EU - Adaptation	28 (F+,T;
R:12-45 Carc.Cat.1-46 Mutagen Cat.2	2)	
PENTANE	109-66-0	1 - 5
EU Hazard Symbols and Risk Phrases	: EU - Adaptation	. 25
(F+,N,Xn; R:12-51-53-65-66-67)		
ISOBUTANE	75-28-2	1 - 5
ISOPENTANE	78-78-4	0.5 - 1.5

EU Hazard Symbols and Risk Phrases: EU - Adaptation 25

(F+,N,Xn; R:12-51-53-65-66-67) N-HEXANE

110-54-3 Less Than 0.4

Ingredient name and classification CAS number Percentage

EU Hazard Symbols and Risk Phrases: EU - Adaptation 25 (F,Xi,Xn,N; R:11-38-48/20-51-53-62 Fert.Cat.3-65-67)

3 HAZARDS IDENTIFICATION

Critical hazards:

Extremely flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Harmful to aquatic organisms. May cause longterm adverse effects in the aquatic environment.

4 FIRST-AID MEASURES

Eye Contact:

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact:

Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation:

If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention. Remove person to fresh air.

Ingestion:

Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention. Do not induce vomiting.

5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

Exposure Hazards:

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition:

Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

Fire-Fighting Procedures:

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head

Special Instructions:

Aerosol container contains flammable material under pressure.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Observe precautions from other sections. Ventilate the area. WARNING! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. If it can be done safely, place the leaking container in an exhaust hood or well- ventilated area. Contain spilled material. Clean up residue. Place depressurised can and clean up wastes in a closed container approved for transportation by appropriate authorities.

Methods for Cleaning up:

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air.

7 HANDLING AND STORAGE

Precautions for Safe Storage:

Store away from heat.

Fire Prevention:

No smoking while handling this material. Flammable liquefied gas. Do not spray near flames or sources of ignition. Aerosol container contains flammable gas under pressure.

Precautions for Safe Handling:

Do not pierce or burn container, even after use.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection:

Avoid eye contact with vapours, mists, or spray.

Hand Protection:

Skin Protection:

Gloves not normally required. Avoid prolonged or repeated skin contact.

Respiratory Protection:

Avoid inhalation of vapours, mists or spray.

Ingestion:

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep out of the reach of children.

Recommended Ventilation:

Use with appropriate local exhaust ventilation. Do not use in a confined area or areas with little or no air movement.

Exposure Limits:

ACETONE (67-64-1)

UK HSE TWA: 500 ppm; 1210 mg/m3 OES
UK HSE STEL: 1500 ppm; 3620 mg/m3 OES

PROPANE (74-98-6)

UK HSE TWA: Asphyxiant OES

DIMETYL ETHER (115-10-6)

UK HSE TWA: 400 ppm, 766 mg/m3
UK HSE STEL: 500 ppm, 958 mg/m3
CMRG TWA Exposure Limit: 1000 ppm

BUTANE (106-97-8)

UK HSE TWA: 600 ppm; 1450 mg/m3 OES UK HSE STEL: 750 ppm; 1810 mg/m3 OES

PENTANE (109-66-0)

UK HSE TWA: 600 ppm; 1800 mg/m3 OES UK HSE STEL: 750 ppm; 2250 mg/m3 OES

ISOPENTANE (78-78-4)

UK HSE TWA: 600 ppm; 1800 mg/m3 OES
UK HSE STEL: 750 ppm; 2250 mg/m3 OES

N-HEXANE (110-54-3)

UK HSE TWA: 20 ppm; 72 mg/m3 OES

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odour: Gas, transparent - white liquid

in aerosol, strong ketone odour.

pH: Not applicable

Boiling point/boiling range: Not applicable

Melting point/melting range: Not applicable

Flash point: -46 C

Autoflammability: Not determined

Vapour pressure: Not determined

Water Solubility: Nil

Specific gravity: 0.65

Vapour density: Greater than 1

Percent volatile: 75 %

10 STABILITY AND REACTIVITY

Conditions to Avoid:

Sparks and/or Flames.

Materials to Avoid:

None known.

Hazardous Decomposition:

Hazardous polymerisation will not occur. Stable.

11 TOXICOLOGICAL INFORMATION

Effects from Eye Contact:

Sprayed material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Effects from Skin Contact:

Mild Skin Irritation: signs/symptoms may include localised redness, swelling, and itching.

Effects from Inhalation:

Sprayed material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, hoarseness, wheezing, breathing difficulty, nose and throat pain, coughing up blood, and non respiratory effects

such as painful and watery eyes.

Effects from Ingestion:

Gastrointestinal Effects: Signs/symptoms may include stomach upset, nausea, vomiting and diarrhea.

Other Effects and Information:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

12 ECOLOGICAL INFORMATION

Other Effects and Information:
Not determined.

13 DISPOSAL CONSIDERATIONS

Product after Use:

As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

Special Instructions:

Incinerate in an industrial or commercial facility. Dispose of completely absorbed waste product in a landfill or facility licenced to handle chemical waste. Incinerate at a facility equipped to handle gaseous waste. Facility must be capable of handling aerosol cans. Since regulations vary, consult applicable regulations or authorities before disposal.

14 TRANSPORT INFORMATION

UN NUMBER:

UN number: UN1950

UK ROAD/SEA FREIGHT (IMO) CLASSIFICATION:

Substance Identification Number: UN1950

Class: 2.0

Packing Group: Not applicable

Proper Shipping Name: Aerosols

CDG-ROAD (if applicable) Not applicable

ADR/RID CLASSIFICATION:

Class: 2.0

Item Number: 5 f

ICAO/IATA CLASSIFICATION:

Class: 2.1

Sub-Risk: Not applicable

Packing Group: Not applicable

Proper Shipping Name: Aerosols, flammable.

15 REGULATORY INFORMATION

Precautionary Label Information:

Symbol(s):

Flame (Extremely Flammable)

Risk Phrases:

Extremely flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Safety Phrases:

Keep away from heat. Keep away from sources of ignition including pilot lights and sparks. No smoking. Do not breathe vapour or spray. Use only in well ventilated areas. Avoid contact with the skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. WARNING! Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 degrees C. Do not pierce or burn, even after use. Do not spray on a naked flame or incandescent material. Avoid release to the environment. Refer to special instructions/safety data sheets. Keep out of the reach of children.

16 OTHER INFORMATION

Regulatory Information:

The following UK Regulations as amended may affect the product as supplied: The Chemicals (Hazard Information and Packaging for

supply) Regulations, as amended. The Carriage of Dangerous Goods

(Classification, Packaging and Labelling) and use of Transportable Pressure Receptacles Regulations 1996, as amended. Carriage of Dangerous Goods by Road Regulations, 1996, as amended. The Petroleum (Consolidation) Act 1928. The Control of Substances Hazardous to Health Regulations 1999 as amended. The Special Waste Regulations 1996, as amended. The Environmental Protection Act, 1990 The Health and Safety at Work Act, 1974.

Reissue date/Reason for reissue.

This is a first issue.

Intended Use of Product:

An aerosol used for fixing most porous and non-porous materials including polystyrene and foams.

The information on this Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law).

The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials.

For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.