C800 Series Specifications



Smallest A3 colour printer, where space is a premium, offering outstanding print quality

If you're looking for a printer that does everything – and does it well, the C800 Series is an ideal choice, especially when space is an issue. Forget old-style huge A3 printers, these will fit into any small office or retail environment, enabling you to print marketing materials in-house, on demand.

The C800 Series will also support all of your everyday printing needs, offering fast and reliable office printing, with document confidentiality.

Key features

- Smallest footprint A3 printer on the market, perfect for retail
- Excellent media flexibility A6 to A3 and up to 1321mm banners
- Up to 35ppm colour print speed
- Fast duplex printing (optional on n variants)
- Paper capacity up to 1,990 sheets and media weights between 64 and 256gsm
- Excellent 1200 x 1200dpi print quality (C843dn)
- Citrix XenApp 7.6 compatibility ideal for virtual network environment



Advanced connectivity

- Wireless Direct offers safe simultaneous connection of wired and wireless networking
- Optional Wireless LAN Module available
- Gigabit Ethernet enables fast transfer of large colour files across the network
- Google Cloud Print 2.0 ready, enabling printing on the move



Easy to use

- Easy to set-up and get started
- Store templates and documents on the device for all users to print without authentication (Shared Print)
- When new features are available you can update the device via the OKI portal



Important security features

- Keep documents confidential with Private Print and optional Card Release#, so users can view all print jobs before selecting which ones to print
- Internet Protocol Security (IPSec) compliance, ensuring securing that documents are safely sent and received



Cost and energy saving

- Print marketing materials in-house, thanks to outstanding print quality and media flexibility
- Deep Sleep mode saves energy, Auto-Off mode automatically powers down to less than 0.5W when not in use
- Toner Save to reduce cost, when printing draft or internal documents
- Duplex printing reduces paper usage
- Mono only printing when colour cartridges are empty
- Free consumables recycling programme
- LED technology means no moving parts for a longer life

_	
A3/A4	~
Colour/Mono	~
Networked/Duplex	~
Prints A6 to 1321mm, up to 256gsm	~
1 – 30 users	~

C823, C833, C843 - Colour and Mono Printers

PRINTER	
Print speed	C823: A4: 23ppm colour/mono; A3: 13ppm colour/mono
	C833/C843: A4: 35ppm colour/mono; A3: 20ppm colour/mono
Time to first print	C823: 14 seconds colour/mono
	C833/C843: 9.5 seconds colour/mono
Warm up time	Up to 25 seconds from power on and up to 20 seconds from power save
INTERFACE AND SOFTWARE	
Connectivity	USB 2.0 Device, 10Base-T/100Base-TX/1000Base-T Ethernet, USB 2.0 Host x 1, Wireless IEEE802.11a/b/g/n (Optional)
-1	C823: PCL6 (XL3.0) and PCL5c, SIDM (IBM-PPR, EPSON-FX), XPS
Printer languages	C833/C843: A4: PCL6 (XL3.0) and PCL5c, PostScript3 emulation, PDF v1.7, SIDM (IBM-PPR, EPSON-FX), XPS
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPv4&v6, NetBIOS over TCP, DHCP, DHCPv6, BOOTP, HTTP, HTTPS, DNS, DDNS, WINS, UPNP, Bonjour, SMTP, POP3, SNMPv1&v3, SNTP, IPP, IPPS, WSD Print, LLTD, IEEEB02.1X, LPR, Port9100, Telnet, FTP, Google Cloud Print, Wireless IEEEB02.11a/b/g/n, WEP, WPA, WPA2, Personal, Enterprise
OS Compatibility ¹	Windows Vista (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows 8 (32-bit & 64-bit) / Server 2012 (64-bit) / Windows 8 (32-bit & 64-bit) / Server 2012 R2 (64-bit) / Windows 10 (32-bit & 64-bit); Linux PPD; Mac OS X 10.8.5 to 10.11
Advanced networking & security	IPv6, 802.1x authentication, SNMP V3, SSL3/TLS HTTPS encryption, Secure Print², Secure Erase², Data Encryption², IP filtering, IPSec
Utility suite ¹	Template Manager ³ , Color Correct, OKI LPR ³ , Color Swatch Utility ³ , smart PrintSuperVision ³ , Print Job Accounting Client, Web Driver Installer ³ , Network Card Setup ⁶ , Configuration Tool ³ , PS Gamma Adjuster ⁷ , PDF Direct Print ^{3/7} , Firmware Update Tool, Profile Assistant ⁶
TYPEFACES	
	C823: Scalable: 87 PCL fonts, PCL Bitmap fonts: LinePrinter, OCR-A/B, USPS ZIP Barcode
Printer fonts	CR33/C843: Scalable: 87 PCL fonts and 80 PostScript fonts, PCL Bitmap fonts: LinePrinter, OCR-A/B, USPS ZIP Barcode
Barcode	10 types of one dimension with 26 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET, 2 types of two dimensions: PDF417, QR code
PRINT QUALITY	
Resolution	C823/C833: ProQ2400 Multi-level technology, 1200 x 600dpi, 600 x 600dpi
	C843: 1200 x 1200dpi
Enhancements	Auto Color Balance, Photo Enhance via Driver (Windows PCL6 driver only)
PAPER HANDLING	
Paper capacity	Tray 1: 300 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; Tray 4: 530 sheets of 80gsm
Maximum paper capacity	1,990 sheets of 80gsm
Paper sizes	Tray 1: A3, A4, A5, A6, B4, B5; Tray 2/3/4: A3, A4, A5, B4, B5; Multi-purpose tray: A3, A4, A5, B4, B5, A6; 11 Envelopes (Com-10, DL, C5,C4), Custom size (up to 1321mm length including banner); Duplex: A3, A4, A5, B4, B5; Custom size: Width 148.5-297mm Length 182-431.80mm
Paper weight	Tray 1: 64 to 220gsm; Tray 2/3/4: 64 to 176gsm; Multi-purpose tray: 64 to 256gsm; Duplex: 64 to 220gsm
Duplex	Standard: C823dn, C833dn, C843dn; Optional: C823n, C833n

GENERAL F	EATURES
-----------	---------

Memory	Standard RAM: 256MB; Maximum RAM: 768MB (C823/C833); Standard RAM: 512MB; Maximum RAM: 768MB (C843)
	Optional SDHC Memory Card ⁴ : 16GB
Environment	Operating temperature/humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)
	Storage temperature/humidty: -10°C to 43°C, 10% to 90% RH
Power supply	Single phase 220-240VAC, frequency 50/60Hz +/-2%
Power consumption	Typical: 700W; Max: 1170W; Idle: 100W; Power Save: <12W; Deep Sleep: <1.0W; Auto-Off: <0.15W
Noise level	Operating: <52dB(A); Standby: 32dB(A) or less; Power save: Background level
Dimensions (WxDxH)	449 x 552 x 360mm
Weight ⁵	37kg approx (n models); 40kg approx (dn models)
Duty cycle	Maximum: 75,000 pages/month; Recommended: 1,500 to 5,000 pages/month
Warranty	3 years extended warranty upon registration within 30 days of purchase
Product order numbers	C823n: 46550701 (2AC) C823dn: 46550703 (2AC) C833n: 46550704 (2AC) C833dn: 46550706 (2AC) C843dn: 46550707 (2AC)

ACCESSORIES (ORDER NUMBERS)

Memory	256MB: 01182907; 512MB: 01182908
SDHC Memory Card ⁴	16GB: 44848903
2nd/3rd/4th paper tray	44713903
Cabinet	01321101
Pedestal with castors	44853903
Duplex	44717603 (Standard on dn models)
Wireless LAN Module	45830202
IC Reader Holder	46539501

CONSUMABLES (ORDER NUMBERS)

	Cyan: 46471103; Magenta: 46471102; Yellow: 46471101; Black: 46471104
Toner cartridges ⁷ * (10,000 pages)	Cyan: 46443103; Magenta: 46443102; Yellow: 46443101; Black: 46443104
Image drums** (30,000 pages)	Cyan: 46438003; Magenta: 46438002; Yellow: 46438001; Black: 46438004
Transfer Belt (80,000 pages)	44846204
Fuser Unit (100,000 pages)	44848805

*Toners: A4 pages yield compliant with ISO/ISC 19798. Printer shipped with toner for 2,500 A4 pages yield compliant with ISO/ISC 19798.

A4 pages yield compliant with ISO/ISC 19798. **Drum: Average number of A4 pages printed.

¹Check local OKI website for latest driver releases and OS compatibility; ²SDHC Memory Card required; ³Windows only; ⁴Secure Digital High Capacity (SDHC) Memory Card supports up to 32GB. OKI is not responsible for any compatibility risk using non OKI genuine SDHC Memory Card; ⁵Including all consumables; ⁶MacOSX only; ⁷C833/C843 only

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.



Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit www.oki.co.uk/warranty

Without registration, the standard pan-European 1 year warranty applies.

#Available through the OKI Firmware Portal in 2017





OKI Systems (UK) LTD.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom +44(0) 1784 274300 www.oki.com/uk

